

Safety Data Sheet

according to WHS regulation

KAESER-Schraubenkompressor-Kühl-Öl SIGMA FLUID MOL

Revision date: 25.04.2023

Page 1 of 10

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

KAESER-Schraubenkompressor-Kühl-Öl SIGMA FLUID MOL

Further trade names

KAESER-Schraubenkompressor-Kühl-Öl SIGMA FLUID MOL, 9.0920.10020, 9.0920.10030, 9.0920.10040, 9.0923.1, 9.5411.1, 9.5411.10010, 9.5832.1

1.2. Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**

cooling lubricant for rotary screw compressor

Uses advised against

Not known

1.3. Details of the supplier of the safety data sheet

Company name:	KAESER Compressors Pty Ltd
Street:	45 Zenith Road
Place:	Dandenong South Melbourne Vic 3175
Telephone:	61 3 97915999
Responsible Department:	msds.au@kaeser.com

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Classification according to WHS Regulation**Acute Tox. 4; H332
Skin Irrit. 2; H315**2.2. Label elements****WHS Regulation****Hazard components for labelling**

Mineral oil (64742-53-6, 64742-54-7, 64742-55-8, 64742-56-9, 64742-65-0, 68037-01-4, 72623-86-0, 72623-87-1, 8042-47-5, 848301-69-9, 68649-12-7, 151006-60-9, 163149-28-8, 64741-88-4, 64741-89-5)

Signal word: Warning**Pictograms:****Hazard statements**H315 Causes skin irritation.
H332 Harmful if inhaled.**Precautionary statements**

P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P302+P352	IF ON SKIN: Wash with plenty of water.
P332+P313	If skin irritation occurs: Get medical advice/attention.

Safety Data Sheet

according to WHS regulation

KAESER-Schraubenkompressor-Kühl-Öl SIGMA FLUID MOL

Revision date: 25.04.2023

Page 2 of 10

P362+P364 Take off contaminated clothing and wash it before reuse.
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P312 Call a POISON CENTER/doctor if you feel unwell.

2.3. Other hazards

The components in this formulation (>0.1%) do not meet the criteria for classification as PBT or vPvB.

SECTION 3: Composition/information on ingredients**3.2. Mixtures****Chemical characterization**

Mineral oil. + Additive

Hazardous components or components with occupational exposure limits (OEL)

CAS No	EC-No.	Chemical name	Quantity
		Mineral Oil*	0 - 90 %
68411-46-1	270-128-1	Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene	1 - 2,9 %

Further Information

The mineral oil contained can be described by one or more of the following numbers. 64742-53-6, 64742-54-7, 64742-55-8, 64742-56-9, 64742-65-0, 68037-01-4, 72623-86-0, 72623-87-1, 8042-47-5, 848301-69-9, 68649-12-7, 151006-60-9, 163149-28-8, 64741-88-4, 64741-89-5

Non-carcinogenic if DMSO extract as measured by IP346 is less than 3% w/w.

SECTION 4: First aid measures**4.1. Description of first aid measures****General information**

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

After inhalation

In case of accident by inhalation: remove casualty to fresh air and keep at rest. When in doubt or if symptoms are observed, get medical advice.

After contact with skin

Take off immediately all contaminated clothing. Rinse skin with water/shower. In case of skin irritation, consult a physician.

After contact with eyes

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. In case of eye irritation consult an ophthalmologist.

After ingestion

Rinse mouth immediately and drink plenty of water. Do NOT induce vomiting. Never give anything by mouth to an unconscious person or a person with cramps. When in doubt or if symptoms are observed, get medical advice.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: Causes mild skin irritation.

ingestion.: Symptoms: few or no symptoms expected. If any, nausea and diarrhoea might occur.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures**5.1. Extinguishing media**

Safety Data Sheet

according to WHS regulation

KAESER-Schraubenkompressor-Kühl-Öl SIGMA FLUID MOL

Revision date: 25.04.2023

Page 3 of 10

Suitable extinguishing media

In case of fire:

Carbon dioxide (CO₂)

Dry extinguishing powder

In case of major fire and large quantities:

Water spray jet

Foam

Unsuitable extinguishing media

High power water jet

5.2. Special hazards arising from the substance or mixtureCan be released in case of fire: Carbon dioxide (CO₂). Carbon monoxide. Nitrogen oxides (NO_x). Sulfur oxides.**5.3. Advice for firefighters**

Wear a self-contained breathing apparatus and chemical protective clothing. (DIN-/EN-Norms: EN469) In case of fire and/or explosion do not breathe fumes.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water. Use water spray jet to protect personnel and to cool endangered containers.

Co-ordinate fire-fighting measures to the fire surroundings.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

For emergency responders: Avoid contact with skin, eyes and clothes. Wear personal protection equipment (refer to section 8).

For non-emergency personnel: Avoid contact with skin, eyes and clothes. Wear personal protection equipment (refer to section 8).

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Prevent spread over a wide area (e.g. by containment or oil barriers). Cover drains.

6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents).

Treat the recovered material as prescribed in the section on waste disposal.

Clean contaminated objects and areas thoroughly observing environmental regulations.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage**7.1. Precautions for safe handling****Advice on safe handling**

Do not breathe vapour/aerosol. Avoid contact with skin, eyes and clothes.

Wear personal protection equipment (refer to section 8).

Special danger of slipping by leaking/spilling product.

Advice on protection against fire and explosion

Usual measures for fire prevention.

Further information on handling

General protection and hygiene measures: See section 8.

7.2. Conditions for safe storage, including any incompatibilities

Safety Data Sheet

according to WHS regulation

KAESER-Schraubenkompressor-Kühl-Öl SIGMA FLUID MOL

Revision date: 25.04.2023

Page 4 of 10

Requirements for storage rooms and vessels

Keep container tightly closed and in a well-ventilated place.
Keep only in original container.
Make sure spills can be contained, e.g. in sump pallets or kerbed areas.
Suitable material for Container: Stainless steel. Polyethylene (HDPE)
Unsuitable materials for Container: PVC (Polyvinyl chloride).

Hints on joint storage

Do not store together with: Gas. Explosive hazardous substances. Oxidising substances (solid). Oxidising substances (liquid). Radioactive substances. Infectious substances.
Keep away from food, drink and animal feedingstuffs.

Further information on storage conditions

Protect against: UV-radiation/sunlight. Heat.

7.3. Specific end use(s)

refer to section 1.

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Exposure limits (AES)**

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
8012-95-1	Oil mist, mineral	-	5		TWA (8 h)	AES

Additional advice on limit values

Air limit values:
Possibility of exposure to: Aerosol
Limit value = 5 mg/m³ - Source: ACGIH

8.2. Exposure controls**Appropriate engineering controls**

Vapours / aerosols should be extracted by suction directly at point of origin.

Protective and hygiene measures

Always close containers tightly after the removal of product. Do not eat, drink or smoke when using this product.
Wash hands before breaks and after work. Take off contaminated clothing.
Do not put any product-impregnated cleaning rags into your trouser pockets.

Eyeface protection

Wear safety glasses; chemical goggles (if splashing is possible).

Hand protection

In case of prolonged or frequently repeated skin contact: Wear suitable gloves.
Standard: AS/NZS 2161 Set: 2008
Suitable material: NBR (Nitrile rubber).
Thickness of the glove material 0,35 mm
Breakthrough time > 480 min.
Check leak tightness/impermeability prior to use. Breakthrough times and swelling properties of the material must be taken into consideration.

Safety Data Sheet

according to WHS regulation

KAESER-Schraubenkompressor-Kühl-Öl SIGMA FLUID MOL

Revision date: 25.04.2023

Page 5 of 10

Skin protection

Protective clothing.

Respiratory protection

With correct and proper use, and under normal conditions, breathing protection is not required.

Respiratory protection necessary at:

Generation/formation of aerosols

Recommended respiratory protection articles: Combination filtering device (AS/NZS 1716:2003).

The filter class must be suitable for the maximum contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If the concentration is exceeded, self-contained breathing apparatus must be used.

Environmental exposure controls

Do not allow uncontrolled discharge of product into the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Liquid
Colour: Light brown
Odour: Characteristic

Test result Test method

pH-Value: Not determined Mineral oil.*

Changes in the physical state

Melting point/freezing point: Not determined Not applicable
>280 °C Estimated

Boiling point or initial boiling point and boiling range:

Sublimation point: not determined

Softening point: not determined

Pour point: -30 °C ASTM D 97

Flash point: 230 °C ASTM D 92

Sustaining combustion: Not sustaining combustion Not applicable

Flammability

Solid: Not applicable

Explosive properties

none

Lower explosion limits: 1 vol. % Not known

Upper explosion limits: 10 vol. % Not known

Auto-ignition temperature: Not determined Not applicable

Self-ignition temperature

Gas: not determined

Decomposition temperature: Not determined Not applicable

Oxidizing properties

none

Vapour pressure: <0,005 hPa Not known
(at 20 °C)

Vapour pressure:

Density (at 15 °C): 0,868 g/cm³ ASTM D 1298

Bulk density: The product has not been tested. Not applicable

KAESER-Schraubenkompressor-Kühl-Öl SIGMA FLUID MOL

Revision date: 25.04.2023

Page 6 of 10

Water solubility:	Not determined	Not applicable
Solubility in other solvents		
Not determined		
Partition coefficient n-octanol/water:	The product has not been tested.	
Viscosity / dynamic:	Not determined	Not applicable
Viscosity / kinematic: (at 40 °C)	46 mm ² /s	ASTM D 445
Flow time:	Not determined	Not applicable
Relative vapour density:	>1[Air=1]	Not known
Evaporation rate:	Not determined	Not applicable
Solvent separation test:	Not determined	
Solvent content:	Not determined	

9.2. Other information

Solid content:	Not determined
----------------	----------------

Auto-ignition temperature: >320 °C

SECTION 10: Stability and reactivity

10.1. Reactivity

No information available.

10.2. Chemical stability

The product is chemically stable under recommended conditions of storage, use and temperature.

10.3. Possibility of hazardous reactions

Reacts with : Oxidizing agents, strong.

10.4. Conditions to avoid

UV-radiation/sunlight. Heat.

10.5. Incompatible materials

Oxidizing agents, strong.

10.6. Hazardous decomposition products

No information available.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Toxicokinetics, metabolism and distribution

No information available.

Acute toxicity

Harmful if inhaled.

Acute oral toxicity LD 50 > 5000 mg/kg (Rat)

Acute toxicity, dermal LD 50 > 5000 mg/kg (Rabbit)

The statement is derived from the properties of the components.

ATEmix calculated

ATE (inhalation vapour) 11,34 mg/l; ATE (inhalation dust/mist) 1,546 mg/l

CAS No	Chemical name			
	Exposure route	Dose	Species	Source
	Mineral Oil*			

Safety Data Sheet

according to WHS regulation

KAESER-Schraubenkompressor-Kühl-Öl SIGMA FLUID MOL

Revision date: 25.04.2023

Page 7 of 10

	inhalation vapour	ATE	11 mg/l		
	inhalation dust/mist	ATE	1,5 mg/l		
68411-46-1	Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene				
	oral	LD50	> 5000 mg/kg	Rat	ECHA Dossier
	dermal	LD50	> 2000 mg/kg	Rat	ECHA Dossier

Irritation and corrosivity

Causes skin irritation.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene:

Skin corrosion/irritation:

Method: OECD Guideline 404 (Acute Dermal Irritation / Corrosion)

Species: Rabbit

Result / evaluation: Not an irritant.; Literature information: ECHA Dossier

Irritant effect on the eye:

Method OECD Guideline 405 (Acute Eye Irritation / Corrosion)

Result / evaluation: Not an irritant.; literature information: ECHA Dossier

Carcinogenicity: negative.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene:

Skin corrosion/irritation:

Method: OECD Guideline 404 (Acute Dermal Irritation / Corrosion)

Species: Rabbit

Result / evaluation: Not an irritant.; Literature information: ECHA Dossier

Irritant effect on the eye:

Method OECD Guideline 405 (Acute Eye Irritation / Corrosion)

Result / evaluation: Not an irritant.

literature information: ECHA Dossier

Aspiration hazard

Based on available data, the classification criteria are not met.

Specific effects in experiment on an animal

There are no data available on the preparation/mixture itself.

SECTION 12: Ecological information

12.1. Toxicity

The product has not been tested.

CAS No	Chemical name				
	Aquatic toxicity	Dose	[h] [d]	Species	Source
68411-46-1	Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene				
	Acute fish toxicity	LC50	> 100 mg/l	96 h Danio rerio	ECHA Dossier
	Acute algae toxicity	ErC50	> 100 mg/l	72 h Desmodesmus subspicatus	ECHA Dossier
	Acute bacteria toxicity	(EC50	>100 mg/l)	3 h activated sludge, domestic	ECHA dossier

Safety Data Sheet

according to WHS regulation

KAESER-Schraubenkompressor-Kühl-Öl SIGMA FLUID MOL

Revision date: 25.04.2023

Page 8 of 10

12.2. Persistence and degradability

Due to its low solubility in water the product is almost completely mechanically separated in biological sewage plants.

Product is partially biodegradable.

Some of the components are poorly biodegradable.

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
68411-46-1	Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene			
	OECD 301B / ISO 9439 / EEC 92/69 annex V, C.4-C	1 %	28	ECHA dossier
	Not readily biodegradable (according to OECD criteria)			

12.3. Bioaccumulative potential

There are no data available on the preparation/mixture itself.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
68411-46-1	Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene	6,66

BCF

CAS No	Chemical name	BCF	Species	Source
68411-46-1	Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene	4176	Cyprinus carpio - 0.01 mg/L	ECHA Dossier

12.4. Mobility in soil

Immobilisation

12.5. Results of PBT and vPvB assessment

The components in this formulation (>0.1%) do not meet the criteria for classification as PBT or vPvB.

12.6. Other adverse effects

No data available

Further information

Do not allow to enter into surface water or drains.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Dispose of waste according to applicable legislation. Consult the local waste disposal expert about waste disposal.

Non-contaminated packages may be recycled.

Contaminated packaging

Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information

Land transport (ADG)

14.1. UN number:

No dangerous good in sense of these transport regulations.

14.2. UN proper shipping name:

No dangerous good in sense of these transport regulations.

14.3. Transport hazard class(es):

No dangerous good in sense of these transport regulations.

14.4. Packing group:

No dangerous good in sense of these transport regulations.

Marine transport (IMDG)

14.1. UN number:

No dangerous good in sense of these transport regulations.

14.2. UN proper shipping name:

No dangerous good in sense of these transport regulations.

Safety Data Sheet

according to WHS regulation

KAESER-Schraubenkompressor-Kühl-Öl SIGMA FLUID MOL

Revision date: 25.04.2023

Page 9 of 10

14.3. Transport hazard class(es): No dangerous good in sense of these transport regulations.**14.4. Packing group:** -**Air transport (ICAO-TI/IATA-DGR)****14.1. UN number:** No dangerous good in sense of these transport regulations.**14.2. UN proper shipping name:** No dangerous good in sense of these transport regulations.**14.3. Transport hazard class(es):** No dangerous good in sense of these transport regulations.**14.4. Packing group:** -**14.5. Environmental hazards**

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

See section 8.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not relevant

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

2010/75/EU (VOC): Not determined

2004/42/EC (VOC): Not determined

The product has been classified according to WHS regulations and categories of the GHS.

Montreal Protocol (Ozone depleting substances):

Mineral oils not listed.

Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene not listed.

The Stockholm Convention (Persistent Organic Pollutants):

Mineral oils not listed.

Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene not listed.

Substance/product listed in the following inventories:

AICS:

Mineral oils: listed

Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene: listed

SECTION 16: Other information**Changes**

Rev. 1,00; 16.02.2015, Initial release

Rev. 2,00; 01.06.2017, Changes in chapter: 2,3,8,9,15

Rev. 3,00; 25.04.2023, Changes in chapter: 2, 3, 9, 11, 12, 15, 16

Abbreviations and acronyms

ACGIH: American Conference of Governmental Industrial Hygienists

ASTM: American Society for Testing and Materials.

ATE: acute toxicity estimate

ADG: The Australian Dangerous Goods Code

AS/NZS: Australian/New Zealand Standards

AICS: Australian Inventory of Chemical Substances

AES: Australian Exposure Standard.

BCF: Bio concentration factor

CAS: Chemical Abstracts Service

d: days

DIN: Norm of the Deutsche Institut für Normung (German Institute for Standardization)

Safety Data Sheet

according to WHS regulation

KAESER-Schraubenkompressor-Kühl-Öl SIGMA FLUID MOL

Revision date: 25.04.2023

Page 10 of 10

EC: Effective Concentration
EG: European Community (Europäische Gemeinschaft)
EN: European Norm
ECHA: European Chemicals Agency
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
GHS: Globally Harmonized System of Classification and Labelling of Chemicals
h: hours
IATA: International Air Transport Association
IBC Code: International Code for the Construction and Equipment of ships carrying Dangerous Chemicals in Bulk
ICAO: International Civil Aviation Organization
IMDG: International Maritime Code for Dangerous Goods
ISO: Norm of the International Standards Organization
IUCLID: International Uniform Chemical Information Database
LC: Lethal concentration
LD: Lethal dose
log K_{ow}: Octanol/water partition coefficient
LOAEL: Lowest observed adverse effect level
LOAEC: Lowest observed adverse effect concentration
MARPOL: Maritime Pollution Convention = Convention for the Prevention of Maritime Pollution from Ships
NOAEL: No observed adverse effect level
NOAEC: No observed adverse effect concentration
OECD: Organisation for Economic Co-operation and Development
PBT: Persistent, bio-cumulative, toxic
UN: United Nation
REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals
RTECS: Registry of Toxic Effects of Chemical Substances
STOT: Specific Target Organ Toxicity
STEL: Short term exposure limit
TWA: Time-weighted average
TLV: Threshold Limiting Value
VOC: Volatile Organic Compounds
vPvB: very persistent and very bio-cumulative
WHS: Work Health and Safety Regulations

Further Information

Classification according to WHS Regulation: - Classification procedure:
Health hazards: Calculation method.
Environmental hazards: Calculation method.
Physical hazards: On basis of test data. and / or calculated and / or estimated.

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)